



P.O. Box 166, Route 100
 Pascoag, Rhode Island 02859
 TEL: (401) 568-3061
 FAX: (401) 568-2273
 www.lockheedwindow.com

CLEAR OPENING FORMULAS FOR VINYL NEW CONSTRUCTION WINDOWS

Most building codes require a minimum, net, clear opening of 5.7 square feet. Furthermore, most codes require a window to have minimum clear width of 22" and a minimum clear height of 24" when opened. **Note: Check your local code to verify compliance.**

MODEL AND FORMULA	MINIMUM FINISHED WINDOW SIZE TO ACHIEVE 5.7 SQ. FEET OF CLEAR OPENING
NUCON® DOUBLE HUNG WINDOW WIDTH MINUS (-) 5.250" WINDOW HEIGHT MINUS (-) 14.0" DIVIDED BY (÷) 2	39-3/8" X 62-1/4"
NUCON® SLIDER (XX) WINDOW WIDTH DIVIDED BY (÷) 2 MINUS (-) 5.510" WINDOW HEIGHT MINUS (-) 5.250"	59-3/8" X 40-00"
NUCON® CASEMENT (X) WINDOW WIDTH MINUS (-) 11.75" WINDOW HEIGHT MINUS (-) 5.000"	34-1/8" X 42-1/4"
NUCON® CASEMENT (XX) WINDOW WIDTH MINUS (-) 15.450" DIVIDED BY (÷) 2 WINDOW HEIGHT MINUS (-) 5.000"	59-5/8" X 42-1/4"
NUCON® CASEMENT (X) * WINDOW WIDTH MINUS (-) 7.250" WINDOW HEIGHT MINUS (-) 5.000"	29-3/8" X 42-1/4"
NUCON® CASEMENT (XX) * WINDOW WIDTH MINUS (-) 10.950" DIVIDED BY (÷) 2 WINDOW HEIGHT MINUS (-) 5.000"	55-1/8" X 42-1/4"

*This window formula is calculated using optional clear opening hinge. Note: This optional hinge prohibits washing of outside vent glass from the interior.